

# MAPEFLOOR WAX REMOVER

Special multi-action, de-waxing detergent for  
Mapelux cross bond, metallic wax



## WHERE TO USE

**Mapefloor Wax Remover** is used in environments for civil use, such as shops, showrooms, apartments, offices etc., to remove surface films of old metallic wax from floors treated with **Mapelux**.

**Mapefloor Wax Remover** has been specially developed to remove metallic wax, especially **Mapelux Lucida** and **Mapelux Opaca** cross bond metallic waxes.

It may also be used for deep-down cleaning and for removing wax from linoleum and/or rubber floors (in the case of old floors with this type of material, test beforehand to check for colour-fastness).

### Some application examples

De-waxing treatment for **Mapelux** protective films on resin floors made using the **Mapefloor System** and/or the **Ultratop System**, including those mixed with **Dynastone Color** or natural aggregates, in environments for civil use before re-waxing the floor.

## TECHNICAL CHARACTERISTICS

**Mapefloor Wax Remover** is a multi-action, low-foaming wax-removal detergent for deep-down cleaning and removal of all types of metallic wax.

It is particularly suitable for removing old films of cross bond metallic wax, such as **Mapelux Lucida/ Mapelux Opaca**.

Its deep-cleansing action attacks all the components in the wax film, and quickly emulsifies residual materials and dirt.

The product contains a minimum of 90% of primary bio-degradable surfactant components and complete aerobic biodegradation, which conforms to Reg. (CE) N° 648/2004.

### How to use

For normal metallic waxes, use at a concentration of from 5 to 10% (1/2-1 l in 10 l of water).

For cross bond metallic waxes such as **Mapelux**, use at a concentration of 15% (1.5 l in 10 l of water).

Use a white cleaning disk, vacuum the surface and then rinse.

## PACKAGING

**Mapefloor Wax Remover** is available in 10 kg cans.

## STORAGE

**Mapefloor Wax Remover** can be stored for 12 months in its original packaging at a temperature between +10°C and +30°C. Protect from frost.

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

**Mapefloor Wax Remover** is corrosive and may cause serious burns. It is also harmful if swallowed and it may irritate the respiratory tract. When applying the product, we recommend the use of protective gloves and goggles and to take the usual precautions for handling chemical products. If the product comes into contact with the eyes or skin, wash immediately with plenty of clean water and seek medical attention.

We also recommend working in well ventilated areas and to protect the respiratory apparatus with a face mask.

For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)	
PRODUCT IDENTITY	
Appearance:	liquid
Colour:	pink
Density (g/cm <sup>3</sup> ):	1.009
Content of active substances (%):	44
pH of concentrated product:	11.7 ± 0.2
Ross Miles depth of foam (ASTM D.459/47):	0 after 3 minutes
Solubility in water:	soluble
Solubility in oil:	insoluble

## WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

**Please refer to the current version of the Technical Data Sheet, available from our website [www.mapei.com](http://www.mapei.com)**

2067-2-2015-gb

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

